



This cost-effective site office folds away for quick transport (up to 5-in-1) and installs quickly and easily.

Designed to meet BCA and other relevant standards

Acoustically superior insulation

Thermal insulation designed for 5 Star Energy Rating

WELS compliant plumbing fittings

Robust steel structure

Easy to transport, quick to install

Flexible in layout and design

FEATURES



EXTERNAL SIZE & TARE WEIGHT	1 x (6096 x 3000 OR 2438 x 2896) at 1900kg approx (forklift pockets - 1500mm centres)
EXTERNAL WALL/ROOF FINISH	1.5mm PPG Corten steel pre-painted panel, engineered steel structure conforming to ISO/ASTM
INTERNAL WALL/CEILING FINISH	3 Ply (0.5mm pre-painted steel + 49mm PU (wall) / 69mm PU (ceiling) + 0.5mm pre-painted steel) or 10mm plasterboard optional
INSULATION	Polyurethane (refrigeration panel); Polystyrene or rock wool optional
FLOOR FINISH	20mm Marine Ply substrate with vinyl finish
DOORS	External - 50mm steel Polyurethane core panel door, steel frame
WINDOWS	Windows with safety glass
ELECTRICAL	Rough-in prepared within integral service ducts
OPTIONAL EXTRAS	Electrical fittings: TV, phone and data points; light fittings and GPOs Plumbing: fixtures to bathroom(s) and kitchenettes; solar HWS Other: office furniture; A/C; termi mesh; adhesive signage; custom paint; local transport; installation. Other options available.

NOTES

20COOFFICE01 Ver: 131008 © Amoveo 2008
Images/plans/specifications are indicative only and subject to confirmation.
Amoveo may amend at its discretion.

