

Amoveo's 2, 3 or 4 sided modules easily connect to create large areas. The base unit can be designed as a class room, admin block, first-aid room, archival facility or any one of Amoveo's Modular Facilities. Modules are easy to transport and install and are perfect for temporary or remote use. Design your own!

- Designed to meet BCA and other relevant standards
- Acoustically superior insulation
- Thermal insulation designed for 5 Star Energy Rating
- Cyclonic structural design and certifications as required
- WELS compliant plumbing fittings
- Robust steel structure
- Easy to transport, quick to install
- Flexible in layout and design

FEATURES



EXTERNAL SIZE & TARE WEIGHT	See reverse for details and indicative Modular Facilities plans
EXTERNAL WALL/ROOF FINISH	1.5mm PPG Corten steel pre-painted panel, engineered steel structure conforming to ISO/ASTM
INTERNAL WALL/CEILING FINISH	3 Ply (0.5mm pre-painted steel + 49mm PU (wall) / 69mm PU (ceiling) + 0.5mm pre-painted steel) or 10mm plasterboard optional
INSULATION	Polyurethane(refrigeration panel); Polystyrene or rock wool optional
FLOOR FINISH	28mm Marine Ply substrate with vinyl finish
DOORS	External - 50mm steel Polyurethane core panel door, steel frame Internal - Aluminium frame and core panel door 50mm
WINDOWS	Windows with safety glass and mounting points for shutters
ELECTRICAL & PLUMBING	Rough-in prepared within integral service ducts
OPTIONAL EXTRAS	Electrical fittings: TV, phone and data points; light fittings and GPOs Plumbing: fixtures to bathroom(s) and kitchen; solar HWS Other: styled roofing; cladding; appliances; furniture; A/C; decking; termi mesh; local transport; installation. Other options available.
NOTES	40FMOMULTI01, 40FMOMULTI02, 40FMOMULTI03 Ver: 131008 © Amoveo 2008 Images/plans/specifications are indicative only and subject to confirmation. Amoveo may amend at its discretion.

Contact Us

Email info@amoveo.com.au


Web www.amoveo.com.au

ABN 56 105 938 798




MULTI-PURPOSE MODULE - FACILITIES

KITCHEN MODULE (40FMOKITCH01)
12192 OR 6096 x 3000 x 2896 at 2500kg - 6000kg approx




COOL ROOM MODULE (40FMOREFRG01)
12192 OR 6096 x 3000 x 2896 at 2500kg - 6000kg approx




SERVERY MODULE (40FMOSERVE01)
12192 OR 6096 x 3000 x 2896 at 2500kg - 6000kg approx



DINING MODULE (40FMODININ01)
12192 OR 6096 x 3000 x 2896 at 2500kg - 6000kg approx




MALE TOILET MODULE (40FMOMTOIL01)
12192 OR 6096 x 3000 x 2896 at 2500kg - 6000kg approx




FEMALE TOILET MODULE (40FMOFTOIL01)
12192 OR 6096 x 3000 x 2896 at 2500kg - 6000kg approx



MALE ABLUTION MODULE (40FMOMABLU01)
12192 OR 6096 x 3000 x 2896 at 2500kg - 6000kg approx



FEMALE ABLUTION MODULE (40FMOFABLU01)
12192 OR 6096 x 3000 x 2896 at 2500kg - 6000kg approx



LAUNDRY MODULE (40FMOLAUND01)
12192 OR 6096 x 3000 x 2896 at 2500kg - 6000kg approx

